
Effetto 14 Square 4 large beams Grey/white

Ernesto Gismondi



IP65 🔲 🔻



LUMINAIRE

- Watt: **11W**

- Voltage: 220V-240V

- Delivered lumens output: 219Im

- CCT: **3000K**- Efficiency: **24%**

- Efficacy: 19.87lm/W

Notes

Wiring to be carried out inside the terminal board by piercing an IP65 membrane grommet suitable for cables with a diameter of 6-13 mm. Painted die-cast aluminium with 3-stage outdoor treatment: nanotechnologies, antioxidant primer, polyester paint. Effective power 10,8W.

DESCRIPTION

Light fixture with 4 light beams using monochromatic LED light sources caracterized by warm colour temperature (3000K) together with light-diffusing lenses which optimize the optical performance of the beams and establish their width. Designed to create geometric lights of scenic effect, it has 4 large beams of 90°. Wall installation. Composed by lighting cap unit and terminal board fixed together by means of locking dowels. Cap in die-cast EN AB-47100 aluminium. Terminal board in reinforced polymer. Watertight gasket in silicone rubber. Locking dowels used outside the fixture in AISI 316 stainless steel. PMMA lenses siliconed flush with the cap to obtain the beam angle opening.

PRODUCT CODE: T42004LW00

FEATURES

- Article Code: T42004LW00

Colour: Grey/whiteInstallation: Wall

Material: Aluminum, composite technopolymer,

methacrylate

- Series: Architectural Outdoor

- Environment: Outdoor

- Area contract: Urban, Outdoor, Residential

- design by: Ernesto Gismondi

DIMENSIONS

Length: cm 14Width: cm 14Height: cm 14

Impact Resistance: **IK10**Glow Wire Test: **650°**

SOURCES INCLUDED



PRODUCT DATA SHEET

PRODUCT CODE: T42004LW00

Category: LedNumber: 1Watt: 11W

Delivered lumens output: **714lm**Color temperature (K): **3000K**

- CRI: **80 typ**

- Color Tolerance: **4SDCM**

- Efficacy: 85lm/W

- Service Life: **L70(14K)>81600**

