

Belvedere Spot Wall Grey




Direct wall attachment. 220/240V power supply included. Included 2 way terminal block 3 phases IP68 (7-12 mm cable). 24V Dimmable version available on request.



Mounting	wall surface
Environment	outdoor
Weight (Kg)	0,90
Light sources available	LED 6W 3000K CRI 80

Colors	<ul style="list-style-type: none"> F001G31A001 - White F001G31A006 - Grey F001G31A018 - Deep Brown F001G31A030 - Black F001G31A033 - Anthracite
---------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------



Beam Angle: 10°


h(m)	E(lx)	D(m)
1	6278	0.17
2	1569	0.34
3	698	0.51
4	392	0.68
5	251	0.84

Luminous flux luminaire
440 lm

Emergency	Without
Transf. availability	included
Transf. mounting	integrated
Insulation Class	II

Number of heads	1
Aiming	adjustable
Light distrib. symmetry	Symmetric

Certificates	<table border="1"> <tr> <td>IP</td> </tr> <tr> <td>65</td> </tr> </table>	IP	65
IP			
65			



Belvedere Spot Wall Grey



Spot Visor
F001Z010000



Spot Visor With Honeycomb
F001Z030000



Spot Visor With Flood Lens
F001Z040000